

## W-Cable for Mini-Line® Grade and Slope Control System

Mini-Line®

The W-cable is a standard Mini-Line® cable used for connection of the Mini-Line® Grade and Slope Control System. It is used to connect a HS301 Handset and two sensor types (grade sensor and slope sensor) to an asphalt paver.

The cable is designed for the environment on pavers. It is made of PUR jacketed coiled cables giving flexibility and protection against chemicals and abrasion. The connectors are fully encapsulated.

The cable lengths specified are the maximum recommended length used.

6-Pin Bayonet Connector

6-Pin Bayonet Connector

6-Pin Bayonet Connector



10-Pin Screw Connector  
Connects to the Machine

### W-Cable Specifications

Part Number	S-50429
Application	Connecting Mini-Line® Grade and Slope Control System to the machine
Power Supply	12/24 Volt Systems (10-30 VDC)
Material	PUR Jacketed Cables
Dimensions, Cable Lengths	1 x 2.2m + 2 x 4.0m
Weight	1.5kg
Storage Temperature	-40°C to 85°C
Operating Temperature	-10°C to 70°C
Connector	1 x 10-Pin Screw, Female 3 x 6-Pin Bayonet, Female 45° Angled



6-Pin Bayonet Connector 45° 10-Pin Screw Connector